



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name

Matador

Article-no

Product/Article	Diameter(mm)	Packaging (pk/ea)	Part Number
Matador Tungsten Th 2%	1.6	10	YLK 116343
Matador Tungsten Th 2%	2.4	10	YLK 116344
Matador Tungsten Th 2%	3.2	10	YLK 116345

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type GTAW (TIG)

GTAW (TIG) Gas tungsten arc welding ISO 6848/AWS SFA A5.12 (or other)

Use Gas shielded Arc welding

1.3 Details of the supplier of the safety data sheet

Supplier

Ceylon Oxygen Limited

Street address

s No. 50, Sri Pannananda Mawatha,

Colombo 15,

Sri Lanka

Telephone

+94 11 4760400, +94 11 2524381

Fax +

+94 11 4615272

Email

Customer.service@ceylonoxygen.com

1.4 Emergency telephone number

Available outside office hours

Yes

Emergency phone number

+94 777 357670

Other

Additional product information

Web site: www.linde.lk





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

Note: When preparing (grinding) and using these electrodes as part of the welding process additional potential hazards are likely: Grinding:

Toxic dusts. Ensure adequate dust extraction, ventilation and dust disposal

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

AWS Classification	W (min.) CAS Number 7440- 33-7	CeO ₂ CAS Number 1306-38-3	La ₂ O, CAS Number 1312- 81-8	ThO ₂ CAS Number 1314-20-1	ZrO ₂ CAS Number 1314-20-1	Other oxides or elements (total max)
EWTh-1	98.3	-	-	0.8-1.2	-	0.5
EWTh-2	97.3	-	-	1.7-2.2	-	0.5

Substance	CAS Number	EG number	REACH Reg	Concentration	Class	fication	Remarks
name			Number	(%)	Hazard	R-phrases	
					attribute		
Tungsten	744-33-7	231-143-9	01-	>95.8		R11	R11 affects only
			2119488910-				powder/dust
			30-0003				
Thorium oxide	1314-20-1	215-225-1		0.8 - 4.2	radioactive	R45-	Substance
						23/24/25-33	affected by
							96/29/Euratom.





Version number: 1

Issued: 2014-01-21

Replaces SDS: 2009-11-23

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Call a physician if symptoms occur.

Skin contact Burns should be treated by a doctor.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Burns from radiation, see doctor.

Ingestion Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

 ${\it 4.3 Indication of any immediate medical attention and special treatment needed}$

Pulmonary irritation.

In the case of lung irritation: Primary treatment by using Corticoide spray, e.g. Auxiloson spray,

Pulmicort-dosage-spray (Auxiloson and Pulmicort are registered trademarks).

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with

diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Low radioactive product

5.3 Advice for fire fighters

Special protective equipment for fire Wear self contained breathing apparatus

fighters





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses. Waste, dust filters and recipients are to de disposed of in a safe and secure way, according to respective national regulations in force. Grey washing or grinding water is to be captured and disposed of.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

For *Personal protection* see section 8. For *Disposal* see section 13. For *Environmental precautions* see section 12. For *Precautions for safe handling* see 7.1.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions	Ensure adequate ventilation for the welder and others. Use respiratory equipment when welding in
	a confined space. Wear protective clothing and eye protection appropriate to arc welding. Remove
	all flammable materials and liquids before welding.
General hygiene	Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	WEL ² 8hr TWA	STEL ^² 15min TWA
Tungsten and compounds (as W)			
Soluble	7440-33-7	1	
Insoluble		5	
Thorium compounds (as Th)	7440-29-1		
Nitrogen dioxide (NO ₂)	10102-44-0	0.5 ppm ³	0.95ppm 3
Ozone (O ₃)	10028-15-6	0.2 ppm ⁴	
Nitrogen monoxide (NO)	10102-43-9	0.5ppm³	0.63ppm 3

8.1.1 Exposure limit values

Germany

Dust exposures TRGS 900

Radiation exposure: Product not listed in TRGS 905. The following dose limits apply for effective

dose in calendar year:

No person at "work", who are not exposed to radiation work 6mSv For persons, who are exposed to radiation during work 20mSv For the complete dose as a consequence of the profession 400mSv

For persons under 18 years of age 6mSv

8.2 Exposure controls

Environmental Exposure Controls - Refer to Section 6 of this SDS

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume concentrations
	within safe limits.
Eye / face protection	Wear eye protection appropriate for welding.
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions.
Other skin protection	Wear body protection which helps to prevent injury from radiation, sparks and electric shock.
Respiratory protection	Use respiratory equipment when welding in a confined space. Wear protective clothing and eye
	protection appropriate to arc welding.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour Grey





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Appearance, physical state Rod

Auto-ignition temperature Not applicable

Auto-inflammability Not auto-flammable

Decomposition temperature Not applicable

Evaporation rate Not applicable

Explosive properties Not explosive

Flammability (solid gas) Not applicable

Flash point Not applicable

Form Fast

Initial boiling point and boiling range Not applicable

Melting point / Freezing point Not applicable

Odour Odourless

Odour threshold Not applicable

Oxidising properties Not applicable

Partition coefficient: n-octanol / water Not applicable

pH value Not applicable

Relative density Not applicable

Solubility Not applicable

Solubility in water Insoluble

Upper / lower flammability or Not applicable

explosive limits

Vapour density Not applicable

Vapour pressure Not applicable

Viscosity Not applicable

9.2 Other information

Not applicable

Other

Density 18.5 to 19.0 g/cm³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not applicable





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

10.2 Chemical stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Contact with strong acids and/or bases; or with halogens (fluorine, chlorine, bromine, iodine and their compounds); or with oxidising agents (e.g. Perchlorate, peroxide, permanganate, chlorates, nitrates, nitrites, chromates); or with alkali/earth alkali metals (e.g. lithium, sodium, potassium, magnesium, calcium) can cause strong reactions (danger of strong exothermal reactions, dange of formation of flammable gases, danger of formation of insalubrious/poisonous substances/gases) must be avoided.

10.6 Hazardous decomposition products

Emerge through oxidation oxids of the product which can evaporate (tungsten trioxide WO_3 CAS 1314-35-8) or be released (thorium oxide ThO_2 CAS 1314-20-1)

 $Welding \ fumes \ and \ gases. \ Additional \ fume \ may \ arise \ from \ coatings \ and \ contaminants \ on \ the \ base \ material.$

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2008)		Concentration of classified fume components
Tungsten and its compounds (W)	7440-33-7	-	-	-	>95.8
Thorium oxide (ThO ₂)	1314-20-1	R23/24/25: Toxic by inhalation, in contact with skin & if swallowed R45: May cause cancer R33: Danger of cumulative effect	Acute Tox 3 Carc. 1B STOT RE 2	H331 H311 H301 H350 H373	0.8 to 4.2
Classification	H phrase	Text			
Acute Tox.: Category 4	H302 H312 H332	Harmful if swallowed Harmful in contact with skin Harmful if inhaled			





Version number: 1

Issued: 2014-01-21

Replaces SDS: 2009-11-23

Carcinogenicity: H350 Category 1B	May cause cancer	
--------------------------------------	------------------	--

The classification information above relates to the fume during use.

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology This product does not feature an acute oral, dermal toxicity or toxicity through inhalation

Irritation Not applicable

Corrosive effects Not applicable

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not applicable

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity Finding after intratracheal application of 50mg tungsten dust per week during 3 weeks on guinea pigs

lead to the conclusion that the substance is relatively inert. Still an effect on the pulmonary tissue

could be proved which must not be neglected.

Reproductive toxicity Not applicable

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere.

LC₅₀ Fish 96h:

15.6mg/L (rainbow trout, oncorhynchus mykiss,28d)

Aluminiumoxide: >100 mg/l Salmo trutta

IC₅₀ Amphibians 72h:

2.9mg/L (toad,gastrophryne carolinensis, 7d)

12.2 Persistence and degradability

Tunsten forms a series of oxohalogenides (e.g. WOCL₄)





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

12.3 Bio accumulative potential

No data vailable

12.4 Mobility in Soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

Not applicable

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations Dispose of any product, residue or packing material according to national and local regulations. Spent

; fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code (EWC) 12 01 13 - welding waste

12 01 04 - non-ferrous metal dust and particles

Section 14. TRANSPORT INFORMATION

14.1 UN number

Land transport (ADR/RID/GGVSEB) UN 2909: radioactive substances, released package, products made of natural thorium; class 7; LQ not

possible

Sea transport (IMDG-Code/GGVSee)

UN 2909: radioactive substances, released package, products made of natural thorium; class 7; LQ not

Air transport (ICAO-TI/IATA-DGR) possible; EmS: F-I, S-S: pack up category A

UN 2909: radioactive substances, released package, products made of natural thorium; class 7; LQ not

possible





Version number: 1

Replaces SDS: 2009-11-23

Issued: 2014-01-21

Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU regulations 67/548/EWF idgF (Dangerous Substances)

99/45/EG idgF (Dangerous Preparations regulations)

96/29/Euratom (only affecting thorium oxide)

Labelling 215-225-1

National regulations EH40/2005 Workplace exposure limits

The Waste Regulations 2011 No. 988

Local laws and regulations should be carefully observed.

15.2 Chemical safety assessment

No data available

Section 16. OTHER INFORMATION

References to key literature and Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).

data sources Regulation (EC) No 1272/2008 of the European Parliament and of the Council.

EH40/2005 Workplace exposure limits.

C&L Inventory database

Annex VI CLP Regulation (EC) 1272/2008

Phrase meaning

H302	Harmful if swallowed
H312	Harmful in contact with skin
H332	Harmful if inhaled

H350 May cause cancer.

Other

Manufacturer's notes Read this Safety Data Sheet carefully and become aware of hazards implied and the safety

information.

End of document