

Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Matador Smooth "Carbon Steel Covered Electrodes" Trade name Article-no Product/Article Diameter(mm) Packaging (kg) Part Number Matador Smooth 2.5 2.5 YLK116319 Matador Smooth 3.2 5 YLK119320 Matador Smooth 4.0 5 YLK119321 Matador Smooth 5.0 5 YLK116339

SMAW Un- and Low-alloyed electrodes Classification: AWS SFA 5.1/5.5 or other

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type Use

Electric arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Street address

Ceylon Oxygen Limited No50,Sri Pannananda Mawatha,

Colombo 15 Sri Lanka.

Telephone

+94 11 4760400, +94 11 2524381

Fax +94 11 4615272

Email Customer.service@ceylonoxygen.com

1.4 Emergency telephone number

Available outside office hours Yes Emergency phone number +94 777357670

Other

Additional product information Web site: www.linde.lk



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

When the product is used in the welding process the most important hazards are: Overexposure to fumes and gases from welding can be dangerous to health. Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire. Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

Mild steel core	Fe	Mn	Cr	Ni		Cu	Si
Typical	98-99	<0.4	<0.027	<0.018		<0.1	<0.26
Flux coating	High Cellulose E6010, 6011	Rutile E6012, 6013	Basic Low Hydrogen E7016, 7018	Rutile Iron Powder E7024	Basic Iron Powder E7028		Cas No.
Limestone and/or Calcium Carbonate	-	<10	20-30	<10	10-20		1317-65-3
Magnesite (total inhalable dust) (respirable dust)	5-10	<5	-	-	-		546-93-0
Cellulose (total inhalable dust) (respirable dust)	25-60	<15	-	-	-		9004-34-6
Iron Oxides (as Fe)	<10	<10	<10	<10			1309-37-6
Inorganic Fluorides (as I	-	<10	10-30	<10	5-15		16984-48-8
Iron powder	-	<10	10-35	10-60	10-60		7439-89-6
Manganese and its Inorganic compounds (a Mn)	as 5-15	5-15	<15	<15	<10		7439-96-5 and others
Rutile/Titanium Dioxide (total inhalable dust) (respirable dust)	10-35	15-60	<10	10-30	<10		13463-67-7
Silicon and Silicon Alloy: (as Si)	S, _	-	<5	<5	<5		7440-21-3
Silicate Binders	<5	<5	<5	<5	<5		1344-09-8
Mica (total inhalable dust) (respirable dust)	<5	<20	<5	<5	<5		12001-26-2
Quartz/Silica Respirable crystalline	<10	<15	5-60	<10	<5		14808-60-7
Kaolin (respirable dust)	-	<20	-	<5	<5		1332-58-7
Other Mineral Silicates	5-30	5-30	5-10	5-30	5-10		1332-58-7



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures	
Inhalation	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for
	breathing. Call a physician if symptoms occur.
Skin contact	Burns should be treated by a doctor.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do. Continue rinsing. Burns from radiation, see doctor.
Ingestion	Contact a doctor if more than an insignificant amount has been swallowed.
4.2 Most important symptoms and effects	s, both acute and delayed
Inhalation	Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

 $4.3 \, {\rm Indication} \, {\rm of} \, {\rm any} \, {\rm immediate} \, {\rm medical} \, {\rm attention} \, {\rm and} \, {\rm special} \, {\rm treatment} \, {\rm needed}$

Not applicable

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for fire fighters

Special protective equipment for fire Wear self contained breathing apparatus fighters

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up Not applicable

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions	Ensure adequate ventilation for the welder and others. Use respiratory equipment when welding in
	a confined space. Wear protective clothing and eye protection appropriate to arc welding. Remove
	all flammable materials and liquids before welding.
General hygiene	Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	ES-TWA	ES-STEL
Total welding fume (particulate)	-	5	
Iron oxide fume (as Fe)	1309-37-1	5	10
Manganese and its inorganic compounds (as Mn)	7439-96-5	1	3



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Silica, amorphous			
(total inhalable dust)	-	6	
(respirable dust)		2.4	
Magnesium oxide (as Mg)			
(total inhalable dust)	1309-48-4	10	
(fume and respirable dust)		4	10
Titanium dioxide			
(total inhalable dust)	13463-67-7	10	
(respirable dust)		4	
Calcium Oxide	1305-78-8	2	
Calcium Silicate			
(total inhalable dust)	1344-95-2	10	
(respirable dust)		4	
Fluoride, inorganic (as F)	16984-48-8	2.5	
Nitrogen dioxide (NO ₂)	10102-44-0	3ppm	5ppm
Ozone (O ₃)	10028-15-6	0.2 ppm	
Nitrogen monoxide (NO)	10102-43-9	25ppm	35ppm

8.2 Exposure controls

Environmental Exposure Control - Refer to Section 6 of this SDS

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume concentrations
	within safe limits.
Eye / face protection	Wear eye protection appropriate for welding.
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions.
Other skin protection	Wear body protection which helps to prevent injury from radiation, sparks and electric shock.
Respiratory protection	Use respiratory equipment when welding in a confined space. Wear protective clothing and eye
	protection appropriate to arc welding.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour	Grey	
Appearance, physical state	Rod	
Auto-ignition temperature	Not applicable	
Auto-inflammability	Not auto-flammable	
Decomposition temperature	Not applicable	
Evaporation rate	Not applicable	



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Explosive properties	Not explosive
Flammability (solid gas)	Not applicable
Flash point	Not applicable
Form	Metal wire with flux coating
Initial boiling point and boiling range	Not applicable
Melting point / Freezing point	Not applicable
Odour	Odourless
Odour threshold	Not applicable
Oxidising properties	Not applicable
Partition coefficient: n-octanol / water	Not applicable
pH value	Not applicable
Relative density	Not applicable
Solubility	Not applicable
Solubility in water	Insoluble
Upper / lower flammability or	Not applicable
explosive limits	
Vapour density	Not applicable
Vapour pressure	Not applicable
Viscosity	Not applicable
9.2 Other information	
	Not applicable
Other	
Density	7.98g/cm ³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity	
	Not applicable
10.2 Chemical stability	
	Stable at normal conditions.
10.3 Possibility of hazardous reactions	
	Not applicable



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Not applicable

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2008)		Concentration of classified fume components
Aluminium oxide (Al)	1344- 28-1	-	-	-	1.8 to 1.2
Barium (Ba)	7440- 39-3	-	-	-	≤0.1
Bismuth oxide (Bi)	12640- 40-3	-	-	-	≤0.1
Calcium (Ca)	1305- 78-8	-	-	-	0.1 to 11.6
Cobalt oxide (Co)	1307- 96-6	R22: Harmful if swallowed R43: May cause	Acute tox 4 (oral)	H302 H317	≤0.1
		sensitisation by contact	Skin sens. 1		
		R45: May cause cancer	Carc. 1B	H350	≤0.1
Chromium III compounds	24613-	R35: Causes severe burns	Skin Corr. 1A	H314	
(as Cr)	89-6	R43: May cause sensitisation by skin contact	Skin Sens. 1	H317	
Copper oxide (Cu)	1317- 38-0	-	-	-	≤0.1
Iron oxide (Fe)	1332- 37-2	-	-	-	11.9 to 54.9
Potassium (K)	7440- 09-7	R34: Causes burns	Skin Corr. 1B	H314	0.6 to 23.8



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Lithium (Li)	7439- 93-2	R34: Causes burns	Skin Corr. 1B	H314	0.1 to 0.8
Magnesium oxide (Mg)	1309- 48-4	-	-	-	0.1 to 5.3
Manganese (Mn)	7439- 96-5	-	-	-	0.7 to 8.2
Molybdenum (Mo)	7439- 98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited evidence of carcinogenic effect	Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3	H351 H319 H335	≤0.1
Sodium (Na)	7440- 23-5	R34: Causes burns	Skin Corr. 1B	H314	0.5 to 8.7
Nickel (Ni)	7440- 02-0	R40: Limited evidence of carcinogenic effect R43: May cause sensitisation by skin contact R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment	Carc. 2 Skin sens 1 STOT RE 1	H351 H317 H372	0.1 to 0.2
Lead (Pb)	7439- 92-1	-	-	-	0.1 to 1.8
Silicon (Si)	7440- 21-3	-	-	-	2.1 to 16.3



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Titanium dioxide (Ti)	13463- 67-7	-	-	-	0.1 to 3.2
Vanadium (V)	7440- 62-2	-	-	-	≤0.1
Zinc (Zn)	7440- 66-6	-	-	-	0.1 to 3.5
Fluoride (F-)	16984- 48-8	-	-	-	0.1 to 21.4

Final fume classification		
Classification	H phrase	Text
Skin corrosion/irritation: Category 1B	H314	Causes severe skin burns and eye damage
Carcinogenicity: Category 1B	H350	May cause cancer

The classification information above relates to the fume during use

Fume analysis: wt %	Fume analysis: wt %
AI 0.1 to 1.2	Ni 0.1 to 0.2
Ca 0.1 to 11.6	Pb 0.1 to 1.8
Fe 11.9 to 54.9	Si 2.1 to 16.3
K 0.6 to 23.8	Ti 0.1 to 3.2
Li 0.1 to 0.8	Zn 0.1 to 3.5
Mg 0.1 to 5.3	F- 0.1 to 21.4
Na 0.5 to 8.7	



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology	Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary oedema
	and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation of the nose,
	throat or eyes.
Irritation	Not applicable
Corrosive effects	Not applicable
Sensitisation	May cause sensitisation by skin contact
Mutagenicity	Not applicable
Carcinogenicity	Welding fumes are possibly carcinogenic to humans
Repeated dose toxicity	Not applicable
Reproductive toxicity	Not applicable

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not applicable

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Not applicable

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

 Disposal considerations
 Dispose of any product, residue or packing material according to national and local regulations. Spent

 ;fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code

Section 14. TRANSPORT INFORMATION

14	1	I IN	number	
14.	1	UN	nunner	

	Not applicable	
14.2 UN proper shipping name		
	Not applicable	
14.3 Transport hazard class(es)		
	Not applicable	
14.4 Packing group		
	Not applicable	
14.5 Environmental hazards		
	Not applicable	
14.6 Special precautions for user		
	Not applicable	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		
	Not applicable	
Other		
Dangerous goods	No	



Version number: 1 Replaces SDS: 2009-11-23 Issued: 2014-01-21

Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU reguations The product does not need to be labelled in accordance with EC directives or respective national laws.

National regulations

Local laws and regulations should be carefully observed.

15.2 Chemical safety assessment

Not applicable

Section 16. OTHER INFORMATION

References to key literature and	Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).	
data sources	a sources Regulation (EC) No 1272/2008 of the European Parliament and of the Council.	
	The Waste regulations 2011 No.988	
	KIFS 2005:7	
	C&L Inventory database	
	Annex VI CLP Regulation (EC) 1272/2008	
Phrase meaning	H314 - Causes severe skin burns and eye damage	
	H350 – May cause cancer.	
Other		
Manufacturer's notes	Read this Safety Data Sheet carefully and become aware of hazards implied and the safety	
	information.	

End of document